

PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



Job Name: _____

Type: _____

Part #: _____

Notes: _____

OXFORD COLLECTION




SPECIFICATIONS:


- 120V INPUT VOLTAGE, 50/60Hz
- HIGH POWER FACTOR
- AMBIENT OPERATING TEMPERATURE
-40°C (-40°F) TO +50°C (122°F)
- ESTIMATED 50,000 HRS L
- 5 YEAR WARRANTY
- DIMMABLE
- ACRYLIC DIFFUSER
- STANDARD PACK QTY: 6
- MOLDED OF DURABLE NON-CORROSIVE
UV RESISTANT RESINS
- UL LISTED FOR WET LOCATIONS
- POST TOPS FIT MOST 3 INCH DIAMETER
POSTS (NOT INCLUDED)




PFX159



PFX160



PFX259



SPECIFICATIONS:

STYLE #	SOURCE/WATTAGE	LUMENS/CCT	BODY	LENS	OPTIONS
PFX259 = POST	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	W = 900lm 3000K C = 1000lm 4000K	B = BLACK W = WHITE	C = CLEAR	T = BRASS TRIM
PFX159 = LONG PFX160 = SHORT	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	W = 900lm 3000K C = 1000lm 4000K	B = BLACK W = WHITE	C = CLEAR	P = PHOTOCELL T = BRASS TRIM

LE800 LED REPLACEMENT PARTS

L08-AC120R-W = 900 LUMEN 3000K ARRAY
L08-AC120R-C = 1000 LUMEN 4000K ARRAY

* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

** ESTIMATED FROM LED SOURCE