

PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



Job Name: _____

Type: _____

Part #: _____

Notes: _____

PBLCSLEDSS

Series 2', 3' 4' & 8' Slim Strips



FEATURES

The PBLCSLEDSS series is a group of 2', 3', 4', and 8' slim strip lights, which are designed as direct replacements for fluorescent strips. The PBLCSLEDSS series is designed to deliver general ambient lighting in a variety of indoor settings, including schools, offices, hospitals and stores, and is the perfect choice for both new construction and retrofits. This high-efficacy luminaire provides long-life and uniform illumination, as well as standard 0-10vdc dimming capability.

- Available in 3500k (warm/neutral white), 4000k (neutral white) and 5000k (cool white) color temperatures.*
- Long-life LEDs provide 122,000 hours of operation with at least 70% of initial lumen output (L70).**
- PBLCSLEDSS2FT provides 2,582 luminaire lumens (129 lumens per watt, LPW) at 3500k; 2,592 luminaire lumens (130 LPW) at 4000k; and 2,613 luminaire lumens (131 LPW) at 5000k.*
- PLCSLEDSS3FT provides 3,138 luminaire lumens (126 LPW) at 3500k; 3,154 luminaire lumens (126 LPW) at 4000k; and 3,186 luminaire lumens (127 LPW) at 5000k.*
- PBLCSLEDSS4FT provides 4,278 luminaire lumens (130 LPW) at 3500k; 4,313 luminaire lumens (131 LPW) at 4000k; and 4,382 luminaire lumens (133 LPW) at 5000k.*
- PBLCSLEDSS8FT provides 8,129 luminaire lumens (131 LPW) at 3500k; 8,131 luminaire lumens (131 LPW) at 4000k; and 8,135 luminaire lumens (131 LPW) at 5000k.*
- Uniform illumination with no visible LED pixelation.
- Universal 120-277 AC voltage (50-60Hz) is standard.
- 0-10vdc dimming capability is standard.
- Power factor > 0.90.
- Total harmonic distortion < 20%.
- Color rendering index > 80.
- Steel housing and acrylic lens.
- Easy installation in new construction or retrofit.

ORDERING INFORMATION


PBLCSLEDSS			
Model	Length	Luminaire Watts	Color Temperature
PBLCSLEDSS	2FT	20	35KMV-ET = 3500k 4KMV-ET = 4000k 5KMV-ET = 5000k
	3FT	25	
	4FT	33	
	8FT	62	




WARRANTY & LISTINGS

- cULus approved for damp locations (-20 C to 50 C / -4 F to 122 F).
- DLC premium approved.
- Flicker-free per IEEE1789-2015 (low risk of adverse effects of flicker at 100% light output level).
- Complies with FCC Part 15, Class B (except for PBLCSLEDSS8FT, which has Class A compliance).
- Complies with IEEE C.62.41-1991, Class A input transient surge protection (2.5kV).
- Complies with RoHS (Restriction on Hazardous Substances) requirements.
- 5-year warranty of all electronics and housing

DIMENSIONS



		PLCSLEDSS2FT	PLCSLEDSS3FT	PLCSLEDSS4FT	PLCSLEDSS8FT
Length	L	22 1/4"	35"	47 3/8"	94 1/4"
Width	W	2 3/8"	2 3/8"	2 3/8"	2 3/8"
Height	H	2 3/4"	2 3/4"	2 3/4"	2 3/4"
Weight (lbs.)		2.4	3.1	3.7	7.5



PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



Job Name: _____

Type: _____

Part #: _____

Notes: _____

ELECTRICAL

Model	Color Temp.	CRI ¹	Luminaire Lumens	Luminaire Watts	Lumens Per Watt	Input Voltage ²	Input Current (A)			Power Factor	THD ³	L ₇₀ Hours
							120V	240V	277V			
PBLCSSLEDSS2FT-20-35KMV-ET	3500k	> 80	2,582	20	129	120-277	0.17	0.08	0.07	> 90%	< 20%	122,000
PBLCSSLEDSS2FT-20-4KMV-ET	4000k	> 80	2,592	20	130	120-277	0.17	0.08	0.07	> 90%	< 20%	122,000
PBLCSSLEDSS2FT-20-5KMV-ET	5000k	> 80	2,613	20	131	120-277	0.17	0.08	0.07	> 90%	< 20%	122,000
PBLCSSLEDSS3FT-25-35KMV-ET	3500k	> 80	3,138	25	126	120-277	0.21	0.10	0.09	> 90%	< 20%	122,000
PBLCSSLEDSS3FT-25-4KMV-ET	4000k	> 80	3,154	25	126	120-277	0.21	0.10	0.09	> 90%	< 20%	122,000
PBLCSSLEDSS3FT-25-5KMV-ET	5000k	> 80	3,186	25	127	120-277	0.21	0.10	0.09	> 90%	< 20%	122,000
PBLCSSLEDSS4FT-35-35KMV-ET	3500k	> 80	4,278	33	130	120-277	0.28	0.14	0.12	> 90%	< 20%	122,000
PBLCSSLEDSS4FT-35-4KMV-ET	4000k	> 80	4,313	33	131	120-277	0.28	0.14	0.12	> 90%	< 20%	122,000
PBLCSSLEDSS4FT-35-5KMV-ET	5000k	> 80	4,382	33	133	120-277	0.28	0.14	0.12	> 90%	< 20%	122,000
PBLCSSLEDSS8FT-65-35KMV-ET	3500k	> 80	8,129	62	131	120-277	0.52	0.26	0.22	> 90%	< 20%	122,000
PBLCSSLEDSS8FT-65-4KMV-ET	4000k	> 80	8,131	62	131	120-277	0.52	0.26	0.22	> 90%	< 20%	122,000
PBLCSSLEDSS8FT-65-5KMV-ET	5000k	> 80	8,135	62	131	120-277	0.52	0.26	0.22	> 90%	< 20%	122,000

¹ Colorrendering index.


² All 50-60Hz.

³ Total harmonic distortion.

⁴ L₇₀ refers to the number of hours at which lumen output declines to 70% of the initial level. L₇₀ hours are IES TM21-11 calculated hours.

PHOTOMETRIC DATA

Model: **PBLCSSLEDSS4FT-35-5KMV-ET (4,382 lumens)**



Candlepower Summary		
	0°	90°
0°	1,252	1,252
10°	1,224	1,236
20°	1,143	1,182
30°	1,015	1,096
40°	858	984
50°	679	852
60°	489	714
70°	292	575
80°	107	446
90°	0	334

Zonal Lumen Summary		
Zone	Lumens	% Fixture
0° - 10°	130	3.0%
10° - 20°	502	11.5%
20° - 30°	1,064	24.3%
30° - 40°	1,743	39.8%
40° - 50°	2,456	56.0%
50° - 60°	3,124	71.3%
60° - 70°	3,685	84.1%
70° - 80°	4,104	93.7%
80° - 90°	4,382	100.0%
180° - 90°	0	0%
180° - 0°	4,382	100.0%

Cone of Light

