

PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



Job Name: _____

Type: _____

Part #: _____

Notes: _____

PFK391/395





RoHS
compliant

SPECIFICATIONS



- 120V INPUT VOLTAGE, 50/60Hz
- HIGH POWER FACTOR
- AMBIENT OPERATING TEMPERATURE -40°C (-40°F) TO +50°C (122°F)
- POLYCARBONATE BASE AND DIFFUSER
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT RESINS
- ESTIMATED 50,000 HRS L70*
- 5 YEAR WARRANTY
- DIMMABLE
- WALL OR CEILING MOUNT
- UL LISTED FOR WET LOCATIONS
- STANDARD PACK QTY: 6



PFK395



PFK391



ORDERING INFORMATION:

MODEL	STYLE	SOURCE/WATTAGE	LUMENS/CCT	BODY	LENS	OPTIONS
PFK						P = PHOTOCELL
	391 = ROUND 395 = SQUARE	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT** LE1200 = 14W POWER INPUT CRI = 80 (TYP) >80 LUMENS PER WATT** LE1800 = 23W POWER INPUT CRI = 80 (TYP) >80 LUMENS PER WATT**	W = 900lm 3000K C = 1000lm 4000K W = 1350lm 3000K C = 1400lm 4000K W = 1850lm 3000K C = 1900lm 4000K	B = BLACK W = WHITE	F = FOSTED W = WHITE	

LE800 LED REPLACEMENT PARTS

L08-AC120R-W = 900 LUMEN 3000K ARRAY
L08-AC120R-C = 1000 LUMEN 4000K ARRAY

LE1200 LED REPLACEMENT PARTS

L12-AC120R-W = 1350 LUMEN 3000K ARRAY
L12-AC120R-C = 1400 LUMEN 4000K ARRAY

LE1800 LED REPLACEMENT PARTS

L18-AC120R-W = 1850 LUMEN 3000K ARRAY
L18-AC120R-C = 1900 LUMEN 4000K ARRAY