

# PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

## POCKET 2 COLLECTION



RoHS  
compliant




### SPECIFICATIONS:

- 120-277V INPUT VOLTAGE, 50/60Hz
- CONSTANT CURRENT AT 700 mA
- CLASS 2 DRIVER POWER FACTOR >.9
- AMBIENT OPERATING TEMPERATURE -40°C (-40°F) TO +40°C (105°F)
- ESTIMATED 50,000 HRS
- THERMALLY PROTECTED LED ARRAY
- FITTER NECK ACRYLIC DIFFUSER
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT RESINS
- UL/CUL LISTED FOR WET LOCATION
- STANDARD PACK QTY: 6

PFP103




EXTENDS: 5 3/4"  
HCMT: 2 3/8"



PFP106




EXTENDS: 6 1/2"  
HCMT: 2 3/8"



PFP109




EXTENDS: 5 3/4"  
HCMT: 2 3/8"



PFP123

EXTENDS: 7"  
HCMT: 4 1/4"



### ORDER INFORMATION:

| STYLE #             | SOURCE/WATTAGE                | LUMENS/CCT      | BODY      | DIFFUSER  |
|---------------------|-------------------------------|-----------------|-----------|-----------|
|                     |                               | C = 912lm 4000K |           | W = WHITE |
| PFP103 = HARBOR     | L900 = 4 CREE LED ARRAY (10W) |                 | B = BLACK |           |
| PFP106 = GLOBE      | 11.3W POWER INPUT             |                 | W = WHITE |           |
| PFP109 = LONG BEACH | CRI = 74 (TYP)                |                 |           |           |
| PFP123 = ACORN      | 80 LUMENS PER WATT **         |                 |           |           |

| L900C LED REPLACEMENT PARTS |                    |
|-----------------------------|--------------------|
| L09C-DC-700-04-R            | = 4 CREE LED ARRAY |
| IG900-DMV-1                 | = LED DRIVER       |

\* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST