

PROlite LED Lighting™

A Division of Emergensee® Lighting, Inc.



Job Name: _____

Type: _____

Part #: _____

Notes: _____

POCKET COLLECTION



RoHS compliant




SPECIFICATIONS:

- 120V INPUT VOLTAGE, 50/60Hz
- HIGH POWER FACTOR
- AMBIENT OPERATING TEMPERATURE -40°C (-40°F) TO +50°C (122°F)
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT RESINS
- UL LISTED FOR WET LOCATIONS
- COTTAGE FIXTURE (FP120) LISTED FOR DAMP LOCATIONS
- ESTIMATED 50,000 HRS L
- 5 YEAR WARRANTY
- DIMMABLE
- ACRYLIC DIFFUSER
- STANDARD PACK QTY: 6




PFP120

EXTENDS: 4 3/4"
HCMT: 6"




PFP123

EXTENDS: 7"
HCMT: 4 1/4"



PFP133

EXTENDS: 5 3/4"
HCMT: 2 3/8"



SPECIFICATIONS:

STYLE #	SOURCE/WATTAGE	LUMENS/CCT	BODY	LENS	OPTIONS
PFP120 = COTTAGE	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	W = 900lm 3000K C = 1000lm 4000K	B=BLACK	W = WHITE	P = PHOTOCELL
PFP123 = ACORN	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	W = 900lm 3000K C = 1000lm 4000K	B = BLACK W = WHITE	W = WHITE	P = PHOTOCELL
PFP133 = BUNGALO	LE800 = 13W POWER INPUT CRI = 80 (TYP) >65 LUMENS PER WATT **	W = 900lm 3000K C = 1000lm 4000K	B = BLACK W = WHITE	C = CLEAR FLEMISH	P = PHOTOCELL

LE800 LED REPLACEMENT PARTS

L08-AC120R-W = 900 LUMEN 3000K ARRAY
L08-AC120R-C = 1000 LUMEN 4000K ARRAY

* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

** ESTIMATED FROM LED SOURCE